



Pneumatic Framing Nailer AN923 / AN943

User-friendly and Well-balanced Framing Nailer.



AN923 For Full Round-Head Nails

AN943 For Clipped-Head Nails

- Built-in inlet filter against intrusion of dust.
- Anti-dry-fire mechanism limits firing.
- Bumper protects body from scratching.
- Rotating dial for adjusting firing depth.
- Safety trigger mode for locking lever.
- Retractable hook



Hook viewed from reverse side of model

Pneumatic Framing Nailer

AN923 / AN943



- Auto Firing Stop
- Dial Depth Adjusting
- Inlet Filter
- Single / Sequential Firing

Capacity	Nail size : 50mm - 90mm (2" - 3-1/2") 64-74pcs (AN923) 60-84pcs (AN943)
Operating air pressure	65 - 120PSIG (4.5 - 8.5kgf / cm ² G)
Dimensions (L x W x H)	559mm x 109mm x 347mm (22" x 4-1/4" x 13-11/16") (AN923) 445mm x 109mm x 365mm (17-7/8" x 4-1/4" x 14-3/8") (AN943)
Net weight	3.9kg (8.7lbs)

Standard Equipment
Oil Supply, Safety Goggles

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

