

Finishing Sander BO3711 / BO3710

Smooth Sanding with lower center of gravity



Ergonomically best possible gripping Trackita



fits user's hand perfectly, providing sure grip and easy handling whether in single- or double-handed operation.









Compact and lightweight design for easy handling and high maneuverability

Variable speed control by dial (BO3711 only)

Sanding speed is variably adjustable to suit workpiece.



Rubberized soft grip provides more comfort and better control while minimizing hand fatigue and pain.



Sturdy cylindrical **Motor Housing**

Available with Dust bag or Dust box



Also connectable to vacuum cleaners with hose




Makita

Photo: BO3711 Easy-to-operate

O

paper clamp ensures easy installation/removal of



Rigid aluminum foot with sponge sleeve

provides high durability and effective vibration-absorbing performance.



Accessories

Punch plate

(For allowing dust extraction through the base)

High dust extraction

Metal: Part No. 192989-7 Plastic: Part No. 194947-9



Pad complete

For use with Abrasive paper Part No. 194929-1 Part No. *194930-6 *hook & loop type



Part No. 135246-0



Dust bag assembly

Part No. 140115-2



Hose Inner dia.28mm Including front cuff 22 Part No. A-34235



Finishing Sander



Double Insulation



Variable Speed (BO3711 only)



Dust Collecting



BO3711 / BO3710

Continuous rating Input Abrasive paper size

Orbits per minute (opm) Dimensions

 $(L \times W \times H)$ Net weight Power supply cord 93 x 185mm (3-5/8" x 7-1/4") 93 x 228mm (3-5/8" x 9") 4,000-11,000 : BO3711

11.000: BO3710 253 x 92 x 154mm (10" x 3-5/8" x 6-1/16") 1.6kg (3.5lbs) 2.0m (6.6ft)

*weight according to EPTA-Procedure 01/2003

Standard Equipment Abrasive Paper, Punch Plate, Dust Bag or Dust Box

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan