



Satisfy Professional's Needs

Multi Tool TM3010C

Tool-less Accessory Change

Lever style lock system allows for quick installation and replacement of the accessories.



Compatible with all OIS accessories
(Oscillating Interface System)



Extra Versatility

Wide selection of accessories available for various applications



The standard equipment may vary by country.



Cutting PVC, FRP pipes



Cutting metals



Wood flush cutting



Sanding and polishing various materials



Cutting tiles



Removing mortar, tile adhesive



Routing joints on wall tiles



Corner cutting



Cutting window putty, silicone

High operation efficiency

Oscillations per minute: up to 20,000 min⁻¹

Oscillating angle: 3.2°



Multi angle setting



Soft start

allows accurate landing of the blade on the surface of workpiece in various applications.

Fully 360° multi angle setting enables use at 12 different angles (each 30°) to allow optimum maneuverability.

Items of standard equipment may vary by country or area.



Wood plunge cutting



Deep plunge cutting

ncy



stant speed control

Ergonomically best possible barrel grip

Variable speed control by dial



Dust extraction system (Option)



ers to position accessories in
ress to tight spaces for



Dust extraction system is available as an option for aggressive dust removal in applications with sanding pad.



Photo : TM3000C



Part No. 196550-2



Cutting plasterboards



Metal flush cutting



Flush cutting of nails



cone



Cutting polystyrene, rubber



Scraping floor tiles

Wide range of accessories available for various applications

Please see "Accessories for Multi Tool" for detailed information on the shape, size, recommended use and material of each blade.

Cutting (plunge cutting)



Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Different from jig saws, etc, able to make a plunge cut in the wall for electrical connection box, lighting, exhaust fan, etc.
- The blade can be positioned in twelve different angles to allow easy operation in tight spaces.

Cutting




Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Able to perform long distance push cut.
- The segment shape allows flush cutting.

Sanding




Applications:

Wood sanding, concrete sanding, or paint removal, etc. with a variety range of abrasive papers.

Benefits:

- Able to sand in corners.
- Connectable to vacuum cleaner with optional dust extraction system.

Removing grout/ Cutting tiles



Applications:

Replacing broken wall or floor tile.

Benefits:

- Less amount of dust scattering thanks to oscillating action.
- The segment shape allows flush cutting.

Scraping



Applications:

Removing mortar, tile adhesive, hardened glue, window putty, caulking, paint, etc.

Benefits:

- Low-profile blade with a narrow tip allows easy removal of caulking, window putty, etc.

Multi Tool

TM3010C

459



- Double insulation
- Variable Speed
- Constant Speed
- Soft Start
- Dust Collecting

Continuous rating Input	320W
Oscillations per minute (opm)	6,000-20,000
Dimensions (L x W x H)	283x68x87mm (11-1/8"x2-11/16"x3-7/16")
Net Weight*	1.6kg (3.7lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment :

Oscillating Multi Tool Accessories

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.



Multi tool
Accessories

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BD-AH