



**Cordless Hammer Driver Drill**  
**Cordless Driver Drill**  
**Cordless Impact Driver**

Satisfy Professional's Needs



Cordless Hammer Driver Drill  
**DHP482**

Cordless Driver Drill  
**DDF482**

Cordless Impact Driver  
**DTD152**

Bits are option.

# High Speed



**DHP482**  
**1,900** High Speed  
 Predecessor model: 1,500



**DDF482**  
**1,900** High Speed  
 Predecessor model: 1,500



**DTD152**  
**2,900** High Speed  
 Predecessor model: 2,300

# Compact overall length for increased maneuverability

← 198mm(7-3/4") DHP482 →



### LED Job light with pre-glow functions

On pulling switch trigger, the light automatically turns on before motor starts turning.



### Compact belt clip



For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.



### Battery

with Battery fuel gauge  
BL1850B: 5.0Ah  
BL1840B: 4.0Ah  
BL1820B: 2.0Ah



BL1850B

BL1850: 5.0Ah  
BL1840: 4.0Ah  
BL1830: 3.0Ah  
BL1820: 2.0Ah  
BL1815N: 1.5Ah



BL1820B

### Fast Charger DC18RC

Charging time 22min.



### Charger DC18SD

Charging time 60min.



## More Torque

DTD152: 165N·m

Predecessor model: 160N·m

DHP482/DDF482: 62N·m

Predecessor model: 50N·m (Hard Joint)

### Ergonomically designed handle with soft grip



**A** In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened according to the U-shape formed between user's thumb and index finger.

**B** Rubberized soft grip provides comfortable grip and more control while minimizing hand fatigue and pain.

### All metal gear construction

All metal gear construction for extra-high transmission durability  
(DHP482, DDF482)



### 21 stages Torque Settings

(DHP482, DDF482)  
Predecessor model: 16 stages



## Cordless Hammer Driver Drill

**DHP482** 13mm (1/2")

440

## Cordless Driver Drill

**DDF482** 13mm (1/2")

440

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 21
- Built-in Job Light
- Carrying Case



DDF482

← 185mm(7-1/4") →

	DHP482	DDF482
<b>Capacity</b>	Steel: 13mm (1/2") Wood: 38mm (1-1/2") Masonry: 13mm (1/2")	Steel: 13mm (1/2") Wood: 38mm (1-1/2") -
<b>Impacts per minute (ipm)</b>	Hi: 0-28,500 Lo: 0-9,000	-
<b>No load speed (rpm)</b>	Hi: 0-1,900 Lo: 0-600	Hi: 0-1,900 Lo: 0-600
<b>Max. fastening torque</b>	Hard / Soft: 62 / 36N.m	Hard / Soft: 62 / 36N.m
<b>Dimensions (L x W x H)</b>	198x79x249mm (7-3/4"x3-1/8"x9-3/4")	185x79x249mm (7-1/4"x3-1/8"x9-3/4")
<b>Net Weight*</b>	1.5kg (3.4lbs) with BL1815N 1.8kg (3.9lbs) with BL1850	1.5kg (3.3lbs) with BL1815N 1.7kg (3.8lbs) with BL1850

**Standard Equipment:** Fast Charger, Battery Cartridge, (+) (-) Bit, Belt clip

## Cordless Impact Driver

**DTD152**

448

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case



← 137mm (5-3/8") →

	DTD152
<b>Capacity</b>	Machine screw: M4 - M8 (5/32 - 5/16") Standard bolt: M5 - M16 (3/16 - 5/8") High tensile bolt: M5 - M12 (3/16 - 1/2") Coarse thread (in length): 22 - 125mm (7/8 - 4-7/8")
<b>Impacts per minute (ipm)</b>	0 - 3,500
<b>No load speed (rpm)</b>	0 - 2,900
<b>Max. fastening torque</b>	165N.m
<b>Dimensions (L x W x H)</b>	137x79x238mm (5-3/8"x3-1/8"x9-3/8")
<b>Net Weight*</b>	1.3kg (2.8lbs) with BL1815N 1.5kg (3.3lbs) with BL1850

**Standard Equipment:** Fast Charger, Battery Cartridge, Belt clip

\*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 2015-07